

Air Products and Chemicals, Inc.

Page 001

Date Prepared: 07/10/03

Date Printed: 08/01/03

MSDS No: 308.0291661-003.004

ACT CMIK' RESIST STRIPPER

---

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: ACT CMIK' RESIST STRIPPER

Product Code: 3015108

General or Generic ID: BLEND

Company

Air Products and Chemicals, Inc.  
7201 Hamilton Blvd.  
Allentown, PA 18195-1501

Emergency Telephone Number:

(800) 523-9374 in Continental  
U.S., Canada and Puerto Rico  
(610) 481-7711 other locations

---

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
N,N-DIMETHYLACETAMIDE	127-19-5	98.0-100.0

---

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Additional symptoms of eye exposure may include: blurred vision.

Skin

Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. May cause mild skin irritation. Symptoms may include redness and burning of skin. Passage of this material into the body through the skin is possible, and skin contact may be harmful.

Continued on next page

MATERIAL SAFETY DATA SHEET

Air Products and Chemicals, Inc.

Page 002

Date Prepared: 07/10/03

Date Printed: 08/01/03

MSDS No: 308.0291661-003.004

ACT CMIK' RESIST STRIPPER

---

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways), lung irritation, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), loss of appetite, visual disturbances, muscle weakness, pain in the abdomen, kidney damage, liver damage.

Target Organ Effects

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: increased iron stores in the spleen, blood abnormalities kidney damage, liver damage, testis damage, Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: blood abnormalities, liver abnormalities, liver damage.

Developmental Information

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Continued on next page

MATERIAL SAFETY DATA SHEET

Air Products and Chemicals, Inc.

Page 003

Date Prepared: 07/10/03

Date Printed: 08/01/03

MSDS No: 308.0291661-003.004

ACT CMIK' RESIST STRIPPER

---

Cancer Information

There is no information available. The chance of this material causing cancer is unknown. This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration.

Other Health Effects

High daily doses of dimethylacetamide, when used as a solvent in cancer treatment, caused central nervous system effects including confusion, disorientation, and hallucinations. Effects were reversible when treatment was stopped. These effects are not expected to be relevant to occupational exposure.

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

---

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Immediately flush skin with water for at least 15 minutes while removing contaminated clothing and shoes. Seek immediate medical attention. Wash clothing before reuse and decontaminate or discard contaminated shoes. Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse. Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Continued on next page

MATERIAL SAFETY DATA SHEET

Air Products and Chemicals, Inc.

Page 004

Date Prepared: 07/10/03

Date Printed: 08/01/03

MSDS No: 308.0291661-003.004

ACT CMIK' RESIST STRIPPER

---

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Note to Physicians

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), liver, kidney, blood-forming system, male reproductive system.

---

5. FIRE FIGHTING MEASURES

Flash Point

146.0 F (63.3 C) TCC

Explosive Limit

(for product) Lower 1.5 Upper 9.7 %

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: acetic acid, amines, carbon dioxide and carbon monoxide various hydrocarbons.

Continued on next page

MATERIAL SAFETY DATA SHEET

Air Products and Chemicals, Inc.

Page 005

Date Prepared: 07/10/03

Date Printed: 08/01/03

MSDS No: 308.0291661-003.004

ACT CMIK' RESIST STRIPPER

---

Fire and Explosion Hazards

Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point.

Extinguishing Media

regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions

Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Health - 2, Flammability - 2, Reactivity - 0

---

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent, or other absorbent material and transfer to hood. Persons not wearing proper personal protective equipment should be excluded from area of spill.

Large Spill

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

Continued on next page

MATERIAL SAFETY DATA SHEET

Air Products and Chemicals, Inc.

Page 006

Date Prepared: 07/10/03

Date Printed: 08/01/03

MSDS No: 308.0291661-003.004

ACT CMIK' RESIST STRIPPER

---

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five-gallon pails and larger metal containers, including tank cars and tank trucks, should be grounded and/or bonded when material is transferred.

Storage

Keep containers closed when not in use.

---

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection

Wear resistant gloves such as: butyl rubber, To prevent skin contact, wear impervious clothing and boots.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Continued on next page

MATERIAL SAFETY DATA SHEET

Air Products and Chemicals, Inc.

Page 007

Date Prepared: 07/10/03

Date Printed: 08/01/03

MSDS No: 308.0291661-003.004

ACT CMIK' RESIST STRIPPER

---

Exposure Guidelines

Component

-----

N,N-DIMETHYLACETAMIDE (127-19-5)  
OSHA PEL 10.000 ppm - TWA (Skin)  
OSHA VPEL 35.000 mg/m3 - TWA (Skin)  
OSHA VPEL 10.000 ppm - TWA (Skin)  
ACGIH TLV 10.000 ppm - TWA (Skin)  
ACGIH TLV 36.000 mg/m3 - TWA (Skin)

---

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

(for component) 331.0 F (166.1 C) @ 760 mmHg

Vapor Pressure

(for component) 2.000 mmHg @ 68.00 F

Specific Vapor Density

3.000 @ AIR=1

Specific Gravity

.946 @ 77.00 F

Liquid Density

7.870 lbs/gal @ 77.00 F

.946 kg/l @ 25.00 C

Percent Volatiles

No data

Evaporation Rate

SLOWER THAN ETHYL ETHER

Continued on next page

MATERIAL SAFETY DATA SHEET

Air Products and Chemicals, Inc.

Page 008

Date Prepared: 07/10/03

Date Printed: 08/01/03

MSDS No: 308.0291661-003.004

ACT CMIK' RESIST STRIPPER

---

Appearance

CLEAR

State

LIQUID

Physical Form

HOMOGENEOUS SOLUTION

Color

CLEAR

Odor

SLIGHT AMINE ODOR

pH

5.0

---

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: acetic acid, amines, carbon dioxide and carbon monoxide  
various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: halogenated hydrocarbons, strong oxidizing  
agents.

Continued on next page



MATERIAL SAFETY DATA SHEET

Air Products and Chemicals, Inc.

Page 009

Date Prepared: 07/10/03

Date Printed: 08/01/03

MSDS No: 308.0291661-003.004

ACT CMIK' RESIST STRIPPER

---

11. TOXICOLOGICAL INFORMATION

No data

---

12. ECOLOGICAL INFORMATION

No data

---

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

---

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

NON-REGULATED BY D.O.T.

Container/Mode:

55 GAL DRUM/TRUCK PACKAGE

NOS Component:

None

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

Other Transportation Information

The DOT Transport Information may vary with the container and mode of shipment.

Continued on next page

MATERIAL SAFETY DATA SHEET

Air Products and Chemicals, Inc.

Page 010

Date Prepared: 07/10/03

Date Printed: 08/01/03

MSDS No: 308.0291661-003.004

ACT CMIK' RESIST STRIPPER

---

15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (UNITED STATES) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR 302.4(a)

None listed

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed(X) Fire(X) Reactive( ) Sudden  
Release of Pressure( )

SARA 313 Components - 40 CFR 372.65

None

OSHA Process Safety Management 29 CFR 1910

None listed

EPA Accidental Release Prevention 40 CFR 68

None listed

International Regulations

Inventory Status

Not determined

State and Local Regulations

California Proposition 65

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the state of California to cause reproductive harm.

TOLUENE

Continued on next page

MATERIAL SAFETY DATA SHEET

Air Products and Chemicals, Inc.

Page 011

Date Prepared: 07/10/03

Date Printed: 08/01/03

MSDS No: 308.0291661-003.004

ACT CMIK' RESIST STRIPPER

---

New Jersey RTK Label Information  
DIMETHYL ACETAMIDE

127-19-5

Pennsylvania RTK Label Information  
ACETAMIDE, N,N-DIMETHYL-

127-19-5

---

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.