

## TMGa SSG

1. IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND THE COMPANY/UNDERTAKING

Product Identifier Trimethylgallium

## Supplier

Akzo Nobel Polymer Chemicals B.V. Stationsstraat 77 PO Box 247 NL-3800 AE Amersfoort The Netherlands T +31 334676767

www.akzonobel.com/polymer

#### E-mail address of person responsible for safety data sheet RegulatoryPC@akzonobel.com

Emergency telephone AkzoNobel Chemicals-Deventer-NL T +31 570 679211 F +31 570 679801

Relevant identified uses of the substance or mixture Semiconductor

# Date of last issue / Revision number

2010/08/06 / 1.03

Chemical family Metal alkyl

## 2. HAZARDS IDENTIFICATION

Reacts violently with water, liberating extremely flammable gases. Spontaneously flammable in air. Causes severe burns.

GHS classification		
Description	Applicable	
Pyrophoric liquid	category 1	
Water contact emits flammable gases	category 1	
Eye irritation	category 1	
Skin corrosion/ irritation	category 1A	

## Pictogram(s) (GHS)



Signal word/Hazard statement(s) GHS	
Code	Description



# TMGa SSG

Signal word: DANGER	
H250.	Catches fire spontaneously if exposed to air.
H260.	In contact with water releases flammable gases which may ignite spontaneously.
H26EUH014.	Reacts violently with water.
H314.	Causes severe skin burns and eye damage.

Precautionary statement(s) (GHS)		
Code	Description	
The precautionary statements marked with a * are mentioned on the label of the packaging of the product.		
P210.	Keep away from heat/sparks/open flames/hot surfaces No smoking.	
P222.	Do not allow contact with air.	
P223.	Keep away from any possible contact with water, because of violent reaction and possible flash fire.	
P231+P232.	Handle under inert gas. Protect from moisture.	
P280d. *)	Wear protective gloves, eye/face protection and protective clothing. *)	
P301+P330+P331.	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.	
P302+P334.	IF ON SKIN: Immerse in cool water/wrap in wet bandages.	
P304+P340.	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.	
P305+P351+P338.	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310. *)	Immediately call a POISON CENTER or doctor/physician. *)	
P363.	Wash contaminated clothing before reuse.	
P378f. *)	Use vermiculite, dry chemical powder or dry sand for extinction. *)	
P402+P404.	Store in a dry place. Store in a closed container.	
P422b. *)	Store contents under nitrogen. *)	
P501a.	Dispose of contents and container according to local regulation.	

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is to be considered as a substance in conformance to EC directives.				
Information on hazardous ingredients				
Chemical description Trimethylgallium				
Composition / information on ingredients				
Number	% w/w	CAS-number	Chemical name	
1	100	001445-79-0	Trimethylgallium	

Number	REACH Registratio n number	EC-number	Classification according to 1272/2008 as amended			Classification according to 67/548/EEC as amended
1		215-897-6	Pyrophoric liquid	category 1	H250 H260 H314	C F R14/15 R17 R35
			Water contact emits flammable gases	category 1		
			Eye irritation	category 1		
			Skin corrosion/ irritation	category 1A		



## <u>TMGa SSG</u>

Other information

Technical pure substance.

#### 4. FIRST AID MEASURES

#### Most important symptoms and effects

Causes severe burns. Causes injury to the cornea and eyelids. Risk of serious damage to eyes. Irritating to respiratory system, may cause delayed pulmonary oedema.

#### Description of first aid measures

#### General

Call a physician immediately.

#### Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Oxygen may additionally be given, by trained personnel, if it is available. Get medical attention immediately.

#### Skin

While wearing impervious gloves and air-tight safety goggles, immediately start continuous flushing of all affected areas on the victim with water for at least 15 minutes. If victim is wearing air-tight safety goggles, do not remove them. Remove contaminated clothing and shoes. If clothing is stuck to the skin after flushing with water, do not remove it. Get medical attention immediately. Wash or destroy clothing. Thoroughly clean or destroy contaminated shoes.

#### Eye

Immediately start continuous flushing of eyes with water for at least 15 minutes. If easy to do, contact lenses should be removed during the flushing, by trained personnel. Hold the eyelids apart during the flushing to ensure rinsing the entire surface of the eye and lids with water. Get medical attention immediately.

#### Ingestion

DO NOT induce vomiting. Get medical attention immediately by calling a physician or a poison control center. If victim is conscious and alert, give a cupful of water. Never give anything by mouth to an unconscious or convulsing person. If vomiting occurs, the patient should lie on their left side while vomiting to reduce the risk of aspiration.

#### Indication of any immediate medical attention and special treatment needed

Persons with pre-existing skin, eye, or respiratory disease may be at increased risk from the irritant or allergic properties of this material.

Irrigate burn area with large amounts of water to decontaminate, if not already done. Chemical burns on the skin should then be treated like thermal burns. Skin reactions may take 24-48 hours to develop. If eyes are affected, flush eyes with buffered or plain irrigating solutions for at least 15 minutes, if not already done. If any ulceration or conjunctival injury is present, have an ophthalmologist examine the patient. Application of cool water helps relieve pain and swelling of both the skin and eyes. If swallowed, do not induce vomiting. Give patient plenty of water to drink. Ingestion of this corrosive material may cause severe ulceration, inflammation, and possible perforation of the gastrointestinal tract. Maintain adequate airway. Aspiration during induced emesis can result in severe lung injury. Contact a Poison Control Center for additional treatment information. Treat any additional effects symptomatically.

#### 5. FIRE-FIGHTING MEASURES

#### Extinguishing media

vermiculite, dry chemical powder, dry sand.

#### Unsuitable extinguishing media

Never use water !!! See also Section: Other information.

foam

halones

#### Hazardous decomposition / combustion products

Product(s) of complete combustion: Gallium oxide, Carbon dioxide.

#### **Protective equipment**

Firefighters must wear fire resistant protective equipment. Wear approved respirator and protective gloves.

## Other information

Evacuate all non-essential personnel. Consider to let it burn out completely. Waterspray may only be used by experienced fire fighters. Cool closed containers with water. After a fire, ventilate thoroughly the area and soak with water, clean the walls and metallic surfaces.



## TMGa SSG

### Fire and explosion hazard

CAUTION: reignition may occur. Vapours produced by incomplete combustion may form explosive mixtures with air. In case of fire and/or explosion do not breathe fumes.

### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions

Do not breathe fumes/vapour. Avoid contact with skin and eyes. For personal protection see Section 8.

#### **Environmental precautions**

Do not allow to enter drains or water courses.

#### Methods and material for containment and cleaning up

Stop leakage if possible. Eliminate all sources of ignition, and do not generate flames or sparks. Take precautionary measures against static discharges. Allow controlled hydrolysis. Isolate spill area. After fire has been extinguished or has been allowed to burn out completely, wait CONSIDERABLE TIME (until smoke is no longer observed). After that, carefully wash spill area with a waterspray.

#### Other information

Ignition will occur. Evacuate personnel to safe area.

#### 7. HANDLING AND STORAGE

## Precautions for safe handling

When using do not eat, drink or smoke. Handle in well ventilated areas. Eliminate all sources of ignition, and do not generate flames or sparks. Take precautionary measures against static discharges. Apply earthing when transferring from one container to another. Avoid contact with moisture and water. Keep under nitrogen. Handle only in closed system. During sampling, disconnecting lines or opening connections, an aluminised suit should be worn. Avoid contact with skin and eyes. Avoid Incompatible materials (See Section 10).

#### Fire and explosion prevention

Spontaneously flammable in air. Do not cut or weld on or near this container even when empty.

#### Conditions for safe storage

Store in accordance with local/national regulations. Keep away from food, drink and animal feedingstuffs. Keep under dry nitrogen containing less than 10 ppm oxygen. Protect product from moisture and wet air. Keep container tightly closed and in a well-ventilated place.

#### Other information

Wash hands thoroughly after handling or contact. Keep working clothing separately and do not take them home.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Ensure good ventilation and local exhaustion of the working area.

#### **Personal protection**

#### Respiratory

In case of insufficient ventilation wear suitable respiratory equipment (respirator with Filter A/p2).

## Hand

impervious gloves.

Eye

Safety glasses and a full face shield. A face shield is preferred over goggles.

#### Skin and body

aluminised suit and protective boots (For further advice contact manufacturer).

#### Other information

Emergency-shower and facilities for rinsing eyes must be accessible. Launder clothes before reuse.

In this country no exposure limit has been established

#### 9. PHYSICAL AND CHEMICAL PROPERTIES



Appearance liquid	
Colour colourless clear	
Boiling point/range 56℃ / 133ፑ	
Melting point/freezing point -16℃ / 3뚜	
Flash point not applicable	
Flammability Extremely flammable. Contact with water liberates extremely flammable gases.	
Explosive properties no	
Oxidising properties no	
Vapour pressure 8.5 kPa (୦୯ / 32年)	
<b>Density</b> 1151kg/m³ (15℃ / 59뚜) Specific gravity = 1.151 (15℃ / 59뚜)	
Bulk density not applicable	
Solubility in water Reacts violently with water.	
Solubility in other solvents Miscible with saturated aliphatic and aromatic hydrocarbons.	
<b>pH value</b> not applicable	
Partition coefficient n-octanol/water not applicable	
Relative vapour density (air=1) not determined	
Non-Pyrophoric Limit Non-Pyrophoric Limit : not determined	
Autoignition temperature Spontaneously flammable in air.	
Upper/lower flammability or explosive limits not applicable	
Volatile % not determined	

10. STABILITY AND REACTIVITY

## Conditions to avoid

In order to prevent thermal decomposition do not overheat.

### **Chemical stability**

Stable under recommended storage and handling conditions (see section 7).

#### Incompatible materials

Avoid contact with moisture and water, alcohols, acids, organic halides and oxygen containing compounds.

## Possibility of hazardous reactions

Polymerization does not occur.



## <u>TMGa SSG</u>

Hazardous decomposition products Gallium, hydrocarbons.

## **11. TOXICOLOGICAL INFORMATION**

## Trimethylgallium

, ,
Acute toxicity
Oral LD50 No data available
Irritation
Skin Corrosive
Eye Corrosive ; Risk of serious damage to eyes.
Respiratory Corrosive

## 12. ECOLOGICAL INFORMATION

No experimental ecological data are available on the substance as such.

## 13. DISPOSAL CONSIDERATIONS

#### Product

Refer to manufacturer/supplier for information on recovery/recycling. Waste disposal in accordance with regulations (most probably controlled incineration).

### Contaminated packaging

According to local regulations. Emptied container might retain product residues. Follow all warnings even after the container is emptied.

#### Other information

For further advice contact manufacturer.

#### 14. TRANSPORT INFORMATION

Land transport
Transport hazard class 4.2
Classification Code SW
RID class 4.2
Packing group
Hazard Identification No. X333
Substance Identification No. 3394
UN number 3394
Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE (Trimethylgallium)
Tunnel code B/E
Required labels 4.2 + 4.3



## <u>TMGa SSG</u>

Subsidiary risk 4.3

Sea transport (IMO / IMDG-code)
Transport hazard class 4.2
Packing group
UN number 3394
EMS F-G, S-M
Marine pollutant no
Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE (Trimethylgallium)
Other information Label(s) : 4.2 + 4.3

Air transport (ICAO-TI / IATA-DGR)

**UN number** Forbidden

15. REGULATORY INFORMATION

 Product label name

 Trimethylgallium

 Labelling according to EC directives

 EC-number

 See section 3

R(isk) phrase(s) (EU classification)		
Code Description		
R14/15.	Reacts violently with water, liberating extremely flammable gases.	
R17.	Spontaneously flammable in air.	
R35.	Causes severe burns.	

S(afety) phrase(s) (EU classification)		
Code	Description	
S06B.	Keep under nitrogen.	
S16.	Keep away from sources of ignition - No smoking.	
S24/25.	Avoid contact with skin and eyes.	
S36/37/39.	Wear suitable protective clothing, gloves and eye/face protection.	
S43B.	In case of fire, use dry chemical powder; never use water.	
S45.	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).	



## TMGa SSG

Classification according to 67/548/EC as ammended			
CORROSIVE (C)	HIGHLY FLAMMABLE (F)		

### Other information

Substance and/or product listed in Directive 96/82/EC.

### German Water Hazard Class (WGK)

This product contains a substance that is not classified by the German authorities. Therefore it should be treated as classified into class WGK 3.

### **16. OTHER INFORMATION**

Relevant hazard statements		
Chemical name	Hazard statement(s) (GHS-classifcat ion)	
Trimethylgallium	H250.	Catches fire spontaneously if exposed to air.
	H260.	In contact with water releases flammable gases which may ignite spontaneously.
	H314.	Causes severe skin burns and eye damage.

R-phrase information			
Chemical name	R(isk) phrase(s) (EU classification)		
Trimethylgallium	R14/15	Reacts violently with water, liberating extremely flammable gases	
	R17	Spontaneously flammable in air	
	R35	Causes severe burns	

History	
Date of printing/ pdf file generated 2013/04/26	
Revision 1.03	



# <u>TMGa SSG</u>

**Composed by** Regulatory Affairs - Europe. Regulatory Affairs - North America, T +1-312-544-7000.

Changes were made in section

2, GHS classification (EU)

This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.